

Issued - 24 June 2011

UK TAF² (Multi) - Linear Shower Channel

This unique marine grade stainless steel channel is designed for UK 'WOOD over JOIST' Floor Structures, as well as concrete floors. Its unique features include an off-set outlet, matching MULTI Trap system & reversible grate, making this flexible high quality shower channel very easy to install. Excellent flow rates & connection options ensures the TAF Multi suits the vast majority of showers installations **E&OE**



PRODUCT CHARACTERISTICS

- Very high quality Marine Grade 316 Stainless Steel offers superior resistance to chemical attack, & is especially suitable for coastal installations
- Outlet is offset by 100mm to allow various joists positions to be catered for, while the trap assembly can be rotated through 360 degrees, & offers 3x trap options, incl. trap water seals of 50, 35 & 30mm
- Surrounding installation flange helps support the 19mm deep channel into common floor boards, & secures the waterproof sealing gasket supplied as standard.
- Removable Stainless Steel grate is reversible offering a flat cover or a 12mm recess to insert matching tiles
- Height adjustable S/Steel Trim Support ensures a foot friendly finish at the channel edge, & allows tile floor finishes with a thickness of between 8mm & 18mm to be used. Thicker sizes can be accommodated with care.
- Installation Sealing Kit comprising surrounding gasket is included as standard, & should be combined with Waterproofing Systems to seal into the floor structure.

APPLICATIONS

UK TAF² Shower Channels are wide collection vessels used within wet room showers, & are offered in various lengths. Suits:

- En-Suites – small bathrooms where space efficiency is at a premium
- High End Designer Bathrooms – Large sizes add to the feeling of space within a shower area
- Refurbishments & New Build
- Floor Structures – Designed for Concrete floors. Can be used on Board over Timber Joist floors when fully supported. Call for advice.

TECHNICAL DATA

- Size Channel, Standard : 500, 600, 700, 800, 900, 1000, 1100, 1200mm
- Size Channel, Special Order : 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000mm
- Visible Size : Approx. 45mm shorter than stated size e.g. 500 is 455mm long visible, when fitted
- Profile : Channel min. 19mm Cross Section, to a max of 22mm
- Waste & Trap : Outlet DN 50mm: Trap 50mm Water Seal (options incl. 30mm & 35mm). See options
- Suitable Floor Covering : Natural Stone or Tile up to 18mm thick. Thicker materials optional.
- Installation Sealing Kit : INCLUDED - Waterproof Sealing Gasket to fit surrounding flange
: Optional - AquaeGUARD or AquaeSEAL Waterproof Membranes ~ See Data Sheets
: A floor gradient of max. 1% > 1.5% must be built into the surrounding floors
- Gradient

MATERIAL

- Channel & Grate : 1.5mm thick 316 Stainless Steel (Marine Grade)
- Trap : ABS
- Install Kit : Self Adhesive Rubberised Fleece Tape

Issued - 24 June 2011

CAPACITY

- Waste & Trap 50mm Seal : Horizontal (38 > 48 Ltrs/Min) location dependant
- Waste & Trap 35mm Seal : Horizontal (31 > 37 Ltrs/Min) location dependant
- Waste & Trap 30mm Seal : Horizontal (28 > 33 Ltrs/Min) location dependant

INSTALLATION INSTRUCTIONS

- See Separate Sheet : Included in Package

PACKAGING

- Cardboard Tube : to suit Shower Channel

CONTENTS

Supplied in Single Tube

- Shower Channel
- Adjustable ABS Trap Housing – Horizontal DN 50mm Outlet
- Trap Funnel & Dish – to create seal of 50mm, 35mm & 30mm
- Waterproof Sealing Gasket – Self Adhesive Rubberised Fleece
- Height Adjustable Trim Support, & supports
- Cover Grate with Reverse option for Tile inserts
- Adjustable Feet (concrete floors), & Earthing Tag
- Installation Instructions

SPECIFICATION – UK TAF² Multi Linear shower channel in 316 S/Steel with installation flange, 3x high flow traps with 360 degree outlet rotation accessed by removable & reversible grate with tile insert option & retained by S/Steel Trim Support adjustable for tile thickness of 8mm > 20mm

Range	Size	ART No.
UK TAF ² Multi	500 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00280
UK TAF ² Multi	600 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00281
UK TAF ² Multi	700 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00282
UK TAF ² Multi	800 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00283
UK TAF ² Multi	900 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00284
UK TAF ² Multi	1000 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00285
UK TAF ² Multi	1100 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00286
UK TAF ² Multi	1200 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00287
UK TAF ² Multi	1300 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00288
UK TAF ² Multi	1400 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00289
UK TAF ² Multi	1500 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00290
UK TAF ² Multi	1600 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00291
UK TAF ² Multi	1700 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00292
UK TAF ² Multi	1800 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00293
UK TAF ² Multi	1900 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00294
UK TAF ² Multi	2000 Long Channel & Trap c/w Trim Support & Reversible Grate	008.00295

E&OE

We reserve the right to alter & amend specifications without prior notice

This is not a specification document & does not guarantee performance

 © Bathroom Engineering[™] September 10
