

Uniclass

L22231:L7315

CI/SfB

94 (52.9)







Build ability

Aesthetics

Value

User Experience

The core values of Bathroom Engineering combine to place the company among the best in the business. Whether you need technical advice, a superb range of design choices, product quality, or simply first class delivery.

John Ruskin, who knew a thing or two about quality, wrote...

"It is unwise to pay too much, but it is worse to pay too little. When you pay too much you lose money, but when you pay too little you sometimes lose everything, because the thing you bought was unable to do the things it was bought to do."

With Bathroom Engineering™ you can be confident you are dealing with the best.

R.D. Sigi Herring Managing Director

Bathroom Engineering™
Priory Park
Chewton Mendip
Somerset
Bath
BA3 4NT
T +44(0)1761 241133

T +44(0)1761 241133 F +44(0)1761 241134

sales@bathroom-engineering.co.uk www.bathroom-engineering.co.uk







FLOOR DRAINS



FLOOR DRAINS

2 - OFF THE SHELF TRAY ...

bathroom

There are 3x types of floor drain, with very different features.

: A long & narrow drain often found along a wall

· Special Situations : Floor drains in unusual shapes that solve specific design problems

 Single Point : A smaller drain, where the floor gradient comes from all sides

All floor drains have key features that provide specific functions. They are:

• The Chassis : The main drain body, that holds together other elements including the

channel, trap, outlet, & grate

: This part of the drain stops bad smells coming up from the sewers The Trap

• The Outlet : The hole where waste water exits to connecting pipes, leading to the

· Removable Grate : This is a cover, that hides the chassis where water is collected before it enters the trap

Whatever your shower drain needs, we have the best solutions.

SYSTEM CHOICE - Why choose bespoke?

bathroom

If all wet room showers serve the same purpose, why choose a bespoke design?

An 'off the shelf' tray system may be easier to order, but offers very limited design options.

1 - BESPOKE SHOWER COMPONENTS ...

To cope with the all bathroom shapes, it has to be reduced and squeezed to fit.

The essential 'envelope' cuts for the tiling takes time to shape, and even longer to fit properly (see above).

Individual components however, designed & built to suit the bathroom space, give a unique and high quality finish. The design will stay current and looks fantastic for a very long time.

The gradients run in one direction without tile cuts, & the whole bathroom says 'quality'.

And, working around site problems is so much easier without the inflexibility of a fixed tray system.

Above all, the experience of using the bathroom will always be luxurious and enjoyable.

INDEX

P6 - PURE Glass - White

P6 - TAF2 Multi DUO

P7 - UK TAF²

P8 - Ultra Tile

P8 - PURE Glass - Black P9 - XERO 83 / XERO 83 Z

P10 - Tegel Multi DUO

P10 - PURE Glass - Green

P11 - Tegel

P12 - Multi FIXT

P12 - Flex

P13 - PURE Tile

P14 - DECO M P14 - DECO Z

P15 - Trapezium

P15 - Round

P15 - Square P16 - AquaeFLOW

P16 - Delta Multi

P16 - Quattro

P17 - Engineering Pack™

P17 - Easy Fix Kits

TIMBER FLOORS

PURE Glass, White

Low profile universal drain with fitted membrane & white glass grate.

Features

Floor Type

- Timber (& Concrete) Floor Finish

Grate Style - Glass, WHITE **Waste Capacity** - 36 Litres / Minute

Waste Outlet - Centre, Single, BS2"

Waterproofing - Factory Fit

Includes

Drain Chassis & Height Adjustable Grate BS2" Outlet with Factory Fit Membrane

<u>Size</u>	<u>Code</u>
PURE Glass, 500mm	008 0049
PURE Glass, 600mm	008 0049
PURE Glass, 700mm	008 0049
PURE Glass, 800mm	008 0049
PURE Glass, 900mm	008 0049
PURE Glass, 1000mm	008 0049
PURE Glass, 1100mm	008 0049
PURE Glass, 1200mm	008 0049



Tech Drawing, see page P.18 TAF² MULTI DUO

TAF² MULTI DUO

Ultra high capacity tile insert drain with fitted membrane and twin traps that rotate to ease installation.

Features

Floor Type

Material

- Timber (& Concrete)

Grate Style Waste Outlet

Waterproofing

- Tile Insert / Steel - Twin, Central - 316 Stainless Steel - Factory Fit

Technical Data

Length Length, Visible Width Build-In Height Foul Air Trap

Trap Connection - BS2" / 50mm

- Nominal,100^m/_m increment - Nominal size, less 45mm - 95mm Visible - 117mm, as standard - 50mm Deep Water Seal

Waste Capacity - 72 Litres / Minute (90+ LPM Theoretical)

Includes

Drain Chassis Tile Insert Grate to fit frame **Height Adjustable Grate Support Frame** BS2" Outlet Connection / Adpator Factory Fitted Waterproof Sealing Collar Access Hook to lift Grate

Instructions **Installation Leveling Set**

Tech Drawing, see page P.18

<u>Size</u>	Code
MultiDUO TAF2, 800mm	008 00180
MultiDUO TAF2, 900mm	008 00181
MultiDUO TAF2, 1000mm	008 00182
MultiDUO TAF ² , 1100mm	008 00183
MultiDUO TAF2, 1200mm	008 00184
MultiDUO TAF2, 1300mm	008 00185
MultiDUO TAF ² , 1400mm	008 00186
MultiDUO TAF2, 1500mm	008 00187
MultiDUO TAF2, 1600mm	008 00188
MultiDUO TAF ² , 1700mm	008 00189
MultiDUO TAF2, 1800mm	008 00190
MultiDUO TAF2, 1900mm	008 00191
MultiDUO TAF2 2000mm	008 00192




LINEAR FLOOR DRAINS

TIMBER FLOORS

This unique marine grade stainless steel channel is designed for UK 'WOOD over JOIST' Floor Structures, as well as concrete floors. It features an off-set outlet, matching MULTI Trap system & reversible grate, making this flexible high quality shower channel very easy to install. **Excellent flow rates & connection** options ensures the TAF Multi suits the vast majority of showers installations.





Low profile tile insert drain for timber joist floors with fitted membrane and high capacity rotating offset trap, to miss joists.

Features

Waste Outlet

Material

Floor Type Floor Finish **Grate Style**

- Timber (& Concrete) - Tile

- Tile Insert / Steel

- Offset, Single, 50mm - 316 Stainless Steel

Waterproofing - Factory Fit

Technical Data

Length - Nominal,100^m/_m increment Length, Visible - Nominal size, less 45mm Width

Build-In Height - 119mm Foul Air Trap

50mm Deep Water Seal Trap Connection - BS2" / 50mm - 48 Litres / Minute Waste Capacity

Includes

Drain Chassis

Tile Insert Grate to fit frame Height Adjustable Grate Support Frame

Rotating Trap BS2" Outlet Connection / Adaptor Factory Fitted Waterproof Sealing Collar Access Hook to lift grate

Instructions
Installation Levelling Leg Set

<u>Size</u> **Code**

JK TAF ² , 500mm	008 00280
JK TAF ² , 600mm	008 00281
JK TAF ² , 700mm	008 00282
JK TAF ² , 800mm	008 00283
JK TAF ² , 900mm	008 00284
JK TAF ² , 1000mm	008 00285
JK TAF ² , 1100mm	008 00286
JK TAF ² , 1200mm	008 00287
JK TAF ² , 1300mm	008 00288
JK TAF ² , 1400mm	008 00289
JK TAF ² , 1500mm	008 00290
JK TAF ² , 1600mm	008 00291
JK TAF ² , 1700mm	008 00292
JK TAF ² , 1800mm	008 00293
JK TAF ² , 1900mm	008 00294
JK TAF ² , 2000mm	008 00295

LINEAR FLOOR DRAINS

CONCRETE (& TIMBER) FLOORS

Low profile floor drain with fixed outlet & 50mm trap. Also features tile insert grate & waterproof sealing membrane.

Features

Floor Type Floor Finish **Grate Style** Waste Outlet Foul Air Trap Material

Concrete (& Timber)

- Fixed, Low Profile

- 50mm Deep Water Seal - 304 Stainless Steel

Waterproofing - Factory Fit

Technical Data

Length Length, Visible Width, Visible

- Nominal, 100^m/_m increment - Nominal, less 34mm

Build-In Height

- 85mm to unfinished floor - 50mm water seal

Foul Air Trap Outlet Connection - 50mm / 2"

- 72mm


Waste Capacity - 42 Litres / Minute

<u>Includes</u>

Drain Chassis Height Adjustable Tile Insert Grate Fixed Outlet with front eject BS2" Outlet Connection / Adaptor Access Hook to lift Grate

Installation Levelling Leg Set Removable Trap with Rodding Access

<u>Size</u>	<u>Code</u>
ULTRA Tile, 500mm	008 00550
ULTRA Tile, 600mm	008 0055
ULTRA Tile, 700mm	008 00552
ULTRA Tile, 800mm	008 00553
ULTRA Tile, 900mm	008 00554
ULTRA Tile, 1000mm	008 0055
ULTRA Tile, 1100mm	008 00556
ULTRA Tile, 1200mm	008 00557
ULTRA Tile, 1300mm	008 00558
ULTRA Tile, 1400mm	008 00559
ULTRA Tile, 1500mm	008 00560
ULTRA Tile, 1600mm	008 0056
ULTRA Tile, 1700mm	008 00562
ULTRA Tile, 1800mm	008 00563
ULTRA Tile, 1900mm	008 00564
ULTRA Tile, 2000mm	008 0056
Tech Drawing, see page P.18	



PURE GLASS - Black

PURE Glass, Black

Universal drain with membrane & black glass grate.

Features

Floor Type Floor Finish **Grate Style** Waste Capacity Waste Outlet

Waterproofing

- Concrete (& Timber)

- Tile - Glass, BLACK - 36 Litres / Minute - Centre, Single, 50mm / 2"

Drain Chassis & Height Adjustable Grate BS2" Outlet with Factory Fit Membrane

Size	Code
PURE Glass, 500mm	008 00490
PURE Glass, 600mm	008 00491
PURE Glass, 700mm	008 00492
PURE Glass, 800mm	008 00493
PURE Glass, 900mm	008 00494
PURE Glass, 1000mm	008 00495
PURE Glass, 1100mm	008 00496
PURE Glass, 1200mm	008 00497
Tech Drawing, see page P.18	





LINEAR FLOOR DRAINS

CONCRETE FLOORS

This stainless steel channel is designed for concrete floors, with very limited space. The unique features make this flexible high quality floor drain very easy to install, & to maintain its high performance. Excellent flow rates & connection options ensure the the vast majority of shower installations can be catered for.







XERO 83 / XERO 83 Z

Slimline floor drain with a choice of traditional grate & the lowest profile allowed under UK building regulations.

Features

Waste Outlet

Floor Type - Concrete Floor Finish **Grate Style**

- Tile - Brushed Stainless Steel

- Central / Single low profile - 304 Stainless Steel - Factory Fit Bonding Collar Waterproofing

Technical Data

- Nominal, 100^m/_m increment Length Length, Visible - Nominal

Width - 60mm Build-In Height - 83^m/_m to finished floor Foul Air Trap

- 50mm Deep Water Seal Outlet Connection - 50mm > BS2" Waste Capacity - 42 Litres / Minute

Includes

Drain Chassis BS2" Outlet Connection / Adaptor Factory Fitted Bonding Collar Access Hook to lift Grate Removable trap c/w rodding access

Instructions **Installation Levelling Leg Set**

XERO 83 Z, 1100mm

XERO 83 Z, 1200mm

<u>Size</u> Code

XERO 83, 500mm	008 0053
XERO 83, 600mm	008 0053
XERO 83, 700mm	008 0053
XERO 83, 800mm	008 0053
XERO 83, 900mm	008 0053
XERO 83, 1000mm	008 0053
XERO 83, 1100mm	008 0053
XERO 83, 1200mm	008 0053
XERO 83 Z, 500mm	008 0054
XERO 83 Z, 600mm	008 0054
XERO 83 Z, 700mm	008 0054
XERO 83 Z, 800mm	008 0054
XERO 83 Z, 900mm	008 0054
XERO 83 Z, 1000mm	008 0054
,	

008 00546

CONCRETE FLOORS

Tegel Multi DUO

Ultra high capacity floor drain with tile insert finish for concrete floors only.

Features

Floor Type Floor Finish **Grate Style Waste Outlet Foul Air Trap**

- Tile - Tile Insert - Double, Central - 50mm Deep Water Seal

Material - 316 Stainless Steel Waterproofing - 'Optional' Easy Fix (P17) **Technical Data**

- Concrete

- Nominal,100^m/_m increment Length - Nominal

Length, Visible **Build-In Height**

- 120^m/_m Foul Air Trap - 360° Rotating 50^m/_mSeal Trap Connection - 50mm > 2"

Waste Capacity - 72 Litres / Minute (90+ LPM Theoretical)


<u>Includes</u>

Drain Chassis Tile Insert Grate, Height Adjustable BS2" Outlet Connection / Adaptor **Access Hook to lift Grate** Instructions

Installation Levelling Leg Set

Size	<u>Code</u>
Tegel Multi DUO, 500mm	008 00133
Tegel Multi DUO, 600mm	008 00134
Tegel Multi DUO, 700mm	008 00135
Tegel Multi DUO, 800mm	008 00136
Tegel Multi DUO, 900mm	008 00137
Tegel Multi DUO, 1000mm	008 00138
Tegel Multi DUO, 1100mm	008 00139
Tegel Multi DUO, 1200mm	008 00140
Tegel Multi DUO, 1300mm	008 00141
Tegel Multi DUO, 1400mm	008 00142
Tegel Multi DUO, 1500mm	008 00143
Tegel Multi DUO, 1600mm	008 00144
Tegel Multi DUO, 1700mm	008 00145
Tegel Multi DUO, 1800mm	008 00146
Tegel Multi DUO, 1900mm	008 00147
Tegel Multi DUO, 2000mm	008 00148

Tech Drawing, see page P.18



PURE GLASS - Green

PURE Glass, Green

Low profile universal drain with fitted membrane & green glass grate.

Features

Floor Type Floor Finish **Grate Style** Waste Capacity Waste Outlet

- Timber (& Concrete) - Tile Glass, GREEN

- 36 Litres / Minute - Centre, Single - Factory Fit Waterproofing


Drain Chassis & Height Adjustable Grate BS2" Outlet with Factory Fit Membrane **Rotating Trap**


Size	Code
PURE Glass, 500mm	008 0049
PURE Glass, 600mm	008 0049
PURE Glass, 700mm	008 0049
PURE Glass, 800mm	008 0049
PURE Glass, 900mm	008 0049
PURE Glass, 1000mm	008 0049
PURE Glass, 1100mm	008 0049
PURE Glass, 1200mm	008 0049
Toch Drawing soo page P19	


LINEAR FLOOR DRAINS

CONCRETE FLOORS

Made from Marine Grade Stainless Steel, this gully is designed for CONCRETE Floors. With a central outlet, matched to the high flow rates from the **MULTI** Trap system, this high quality shower channel is easy to install. The special 'tile insert' grate is designed to be filled with sections of floor tile, resulting in a discrete channel hidden in the floor.







Simple concrete floor shower drain with high capacity rotating trap & tile insert

Features

Floor Type Floor Finish - Concrete **Grate Style** - Tile Insert **Waste Outlet** - Central / Single Material - 316 Stainless Steel Waterproofing - 'Optional' Easy Fix (P17) Foul Air Trap 50mm Deep Water Seal

Technical Data

Length Nominal,100^m/_m increment Length, Visible Width - Nominal

- 98^m/_m Build-In Height - 120^m/_m

Waste Capacity - 48 Litres/Minute Trap Connection - DN50> BS2" Rotates 360° Foul Air Trap - 50mm Deep

Includes

Drain Chassis Height Adjustable Tile Insert Grate Rotating Trap BS2" Outlet Connection / Adaptor **Access Hook to lift Grate** Instructions Installation Levelling Leg Set

Size	Code
Tegel Drain, 500mm	008 00250
Tegel Drain, 600mm	008 00251
Tegel Drain, 700mm	008 00252
Tegel Drain, 800mm	008 00253
Tegel Drain, 900mm	008 00254
Tegel Drain, 1000mm	008 00255
Tegel Drain, 1100mm	008 00256
Tegel Drain, 1200mm	008 00257
Tegel Drain, 1300mm	008 00234
Tegel Drain, 1400mm	008 00235
Tegel Drain, 1500mm	008 00236
Tegel Drain, 1600mm	008 00237
Tegel Drain, 1700mm	008 00238
Tegel Drain, 1800mm	008 00239
Tegel Drain, 1900mm	008 00240
Tegel Drain, 2000mm	008 00241

CONCRETE FLOORS

Top specifiation high capacity traditional style floor drain for concrete floors. Optional grating upgrades.

- Concrete

- Traditional Grid

- Central / Single

- 48 Litres / Minute

- 316 Stainless Steel

- Tile

Features

Floor Type Floor Finish **Grate Style**

Waste Capacity Waste Outlet Foul Air Trap Material

Waterproofing Includes

Drain Chassis Rotating Trap Height Adjustable Grate BS2" Outlet Connection / Adaptor Orange Hook & Instructions Installation Levelling Leg Set

Tech Drawing, see page P.18

Code 008 00480 Multi FIXT, 500mm Multi FIXT, 600mm 008 00481 Multi FIXT, 700mm 008 00482 Multi FIXT, 800mm 008 00483 Multi FIXT, 900mm 008 00484 Multi FIXT, 1000mm 008 00485 Multi FIXT, 1100mm 008 00486 Multi FIXT, 1200mm 008 00487 Multi FIXT, 1300mm 008 00488 Multi FIXT, 1400mm 008 00489 Multi FIXT, 1500mm 008 00490 Multi FIXT, 1600mm 008 00491 Multi FIXT, 1700mm 008 00492 Multi FIXT, 1800mm 008 00493 Multi FIXT, 1900mm 008 00494 Multi FIXT, 2000mm 008 00495





Elementry floor drain with traditional grate

Features

Floor Type Floor Finish **Grate Style** Waste Capacity **Waste Outlet** Foul Air Trap **Material** Waterproofing

- Concrete

- Traditional Grid - 26 Litres / Minute - Central / Single - 50mm Deep Water Seal - 316 Stainless Steel - 'Optional' Easy Fix (P17)

<u>Includes</u>

Drain Chassis Height Adjustable Grate **Rotating Trap BS2**" Outlet Connection / Adaptor **Access Hook to lift Grate** Instructions Installation Levelling Leg Set

<u>Size</u>	<u>Code</u>
Flex, 500mm	008 0022
Flex, 600mm	008 0022
Flex, 700mm	008 0022
Flex, 800mm	008 0022
Flex, 900mm	008 0022
Flex, 1000mm	008 0022
Flex, 1100mm	008 0022
Flex, 1200mm	008 0022


Tech Drawing, see page P.18


LINEAR FLOOR DRAINS


TIMBER (& CONCRETE) FLOORS

Specially designed to embed tiles into a height adjustable grate, PURE TILE is a unique stainless steel shower gully for all floor structures.

This flexible shower drain is very easy to install & offers premium quality waterproofing protection fitted at the factory. Good flow rates ensures that PURE TILE suits the majority of showers installations.







PURE Tile

Low profile floor drain with rotating trap, waterproof sealing membrane & tile insert grate.

Features

Floor Type Floor Finish - Timber (& Concrete) - Tile Insert **Grate Style**

- Centre, Single 360° - 304 Stainless Steel **Waste Outlet** Material Waterproofing - Factory Fitted

Technical Data

Length - Nominal,100^m/_m increment Length, Visible - Nominal, less 34mm Width

Build-In Height - 100^m/_m to unfinished floor Foul Air Trap - 50mm Deep Water Seal Trap Connection - 50mm > 2' Waste Capacity - 36 Litres / Minute

Includes

Drain Chassis Height Adjustable Tile Insert Grate Rotating Trap
BS2" Outlet Connection / Adaptor Factory Fitted Waterproof Sealing Collar Access Hook to lift Grate **Hair Stopper** Instructions Installing Levelling Leg Set

<u>Size</u>	<u>Code</u>
PURE Tile, 500mm	008 00480
PURE Tile, 600mm	008 00481
PURE Tile, 700mm	008 00482
PURE Tile, 800mm	008 00483
PURE Tile, 900mm	008 00484
PURE Tile, 1000mm	008 00485
PURE Tile, 1100mm	008 00486
PURE Tile, 1200mm	008 00487

LINEAR FLOOR DRAINS

Traditional grate fitted to low profile chassis with factory fit waterproofing membrane.

- Polished Stainless Steel

- 36 Litres / Minute

- 304 Stainless Steel

- Centre, Single - 50mm Deep Water Seal

- Factory Fit

Floor Type - Timber (& Concrete) Floor Finish

Grate Style Waste Outlet

Waste Capacity Foul Air Trap Waterproofing

<u>Includes</u> Drain Chassis Height Adjustable Grate

Rotating Trap BS2" Outlet Connection / Adaptor Factory Fitted Waterproof Sealing Collar Access Hook to lift Grate

Hair Stopper Instructions

Installation Levelling Leg Set

<u>Size</u>	<u>Code</u>
DECO M, 500mm	008 00210
DECO M, 600mm	008 00211
DECO M, 700mm	008 00212
DECO M, 800mm	008 00213
DECO M, 900mm	008 00214
DECO M, 1000mm	008 00215
DECO M, 1100mm	008 00216
DECO M, 1200mm	008 00217
Tech Drawing see page P18	





DECOZ

Low profile drain with factory fit waterproof membrane & sleek stainless steel grate.

<u>Features</u>

Floor Type Floor Finish **Grate Style Waste Capacity Waste Outlet Foul Air Trap Material** Waterproofing

- Timber (& Concrete) - Tile

- Brushed Stainless Steel - 36 Litres / Minute - Centre, Single

- 50mm Deep Water Seal - 304 Stainless Steel - Factory Fit

<u>Includes</u>

Drain Chassis Height Adjustable Grate Rotating Trap BS2" Outlet Connection / Adaptor Factory Fitted Waterproof Sealing Collar Access Hook to lift Grate Hair Stopper Instructions Installation Levelling Leg Set

Size	<u>Code</u>
DECO Z, 500mm	008 00470
DECO Z, 600mm	008 00471
DECO Z, 700mm	008 00472
DECO Z, 800mm	008 00473
DECO Z, 900mm	008 00474
DECO Z, 1000mm	008 00475
DECO Z, 1100mm	008 00476
DECO Z, 1200mm	008 00477
Tech Drawing, see page P.18	



FLOOR DRAINS

SPECIAL SITUATION

Code

008 00231

008 00232

High flow floor drain that fits between angled walls. 2x size options.

Features

Floor Type Floor Finish - Timber & Concrete - Tile **Grate Style** - Traditional Grid **Waste Outlet** - Central / Single Foul Air Trap - 50mm Deep Water Seal Waste Capacity - 48 Litres / Minute

<u>Includes</u>

Drain Chassis Rotating Trap BS2" Connection / Adaptor Grating Instructions

Size

Trapezium, 300mm Trapezium, 700mm

Tech Drawing, see page P.18





Curved floor drain with traditional grate.

<u>Features</u>

Floor Type - Concrete

Floor Finish **Grate Style Waste Capacity**

Waste Outlet

Foul Air Trap

- Traditional Grid - 26 Litres / Minute - Central / Single

- 50mm Deep Water Seal

Includes

Drain Chassis Rotating Trap BS2" Connection / Adaptor Instructions **Installation Levelling Feet**

<u>Size</u>

Round FLEX, R=550mm Round MULTI, R=550mm

008 00233 008 00299

Code

L shaped linear floor drain with traditional

Features

Floor Type Floor Finish **Grate Style Waste Capacity**

- Concrete - Tile - Traditional Grid

- 26 Litres / Minute Waste Outlet - Central / Single **Foul Air Trap** - 50mm Deep Water Seal

Includes

Drain Chassis & Rotating Trap Installation Levelling Feet Instructions BS2" Connection / Adaptor

Size Square MULTI, 900mm Square MULTI, 1000mm

Square FLEX . 900mm Square FLEX, 1000mm

Code 008 00460 008 00461 008 00462 008 00463





SINGLE POINT DRAINS

ALL FLOORS

AquaeFLOW

Push fit single point floor drain comes with 50mm foul air trap & fits directly into soil

Features

Floor Type Floor Finish - Tile

Grate Style - Traditional Grid

Waste Capacity - 80 Litres / Minute Foul Air Trap - 50mm Deep Water Seal

<u>Includes</u>

Body Grate

Trap Components

Instructions

Size 120mm PUSH FIT 4" Soil Std 011 00340 120mm PUSH FIT 4" Soil CUBE 011 00341 120mm TIMBER Floor Std 011 00342 120mm TIMBER Floor CUBE 011 00343

Tech Drawing, see page P.18





Delta Multi

traditional grates.

Features

Floor Type Floor Finish

Grate Style Foul Air Trap Waste Capacity

Includes

Grating Tran

Size

200mm Delta Multi ZERO 200mm Delta Multi TILE 240mm Delta Multi

Corner floor drain with tile insert or

- Timber (& Concrete)

- Traditional Grid / Tile

- 50mm Deep - 48 Litres / Minute

Chassis Instructions

Code

008 00228 008 00229 008 00230

Tech Drawing, see page P.18

FLOOR DRAINS

INSTALLATION SYSTEMS

Engineering Pack

Universal kit to help build bespoke showers in timber (& concrete) floors. Can be used with individual floor drain components of any make or brand.

Supplied as a kit of 2x parts.

- Gradient Boards (eForm™ 22) - to build correct fall into the floor
- Waterproofing (Choice of 2x Systems)
 AquaeGUARD™ Professional Membrane (P21)
- AquaeSEAL™ Waterproof Gel (P20)

- Gradient Boards Kits to suit standard eForm™ 22 drain lengths drain lengths
 - Hard Core Polymer
 - board
 - Gradient falls from 22mm to 6mm
 - Factory coating applied - Instant robust board, ready to be sealed into floor

Waterproofing

- Min of 5sq. M enough for popular shower sizes Very easy to use
- Upgrade to extra
- waterproofing if required

Code

- Choice of 2x premium
- AquaeGUARD™ AquaeSEAL™

<u>Includes</u>

Size

Gradient Board Floor Former Waterproofing 5sqm Instructions

<u>0126</u>	<u>ooue</u>
AquaeGUARD >1000mm	099 00194
AquaeGUARD >1350mm	008 00195
AquaeGUARD >1700mm	008 00196
AquaeGUARD >2000mm	008 00197
Upgrade by 5 Sq. M	008 00198
AquaeSEAL > 1000mm	008 00064
AquaeSEAL > 1350mm	008 00065
AquaeSEAL > 1700mm	008 00066
AquaeSEAL > 2000mm	008 00067
Upgrade by 5 Sq. M	008 00068
* swap Model A for Model V	ASK I



3x sizes of square single point drain with 3x grate options & fitted membrane.

Features

- Timber (& Concrete) Floor Type Floor Finish - Tile

- Traditional / Tile / Glass **Grate Style** Waste Capacity
Foul Air Trap - 48 Litres / Minute

- 50mm Deep Water Seal

Includes

Chassis & Grate Trap & Instructions

<u>Size</u>	<u>Code</u>
100mm Quattro TILE	008 00150
100mm Quattro ZERO	008 00151
100mm Quattro GLASS	008 00152
150mm Quattro TILE	008 00153
150mm Quattro ZERO	008 00154 008 00155
150mm Quattro GLASS	
200mm Quattro TILE	008 00156
200mm Quattro ZERO	008 00157 008 00158
200mm Quattro GLASS	000 00 130
Tech Drawing, see page P.18	





Waterproof sealing membrane with stretch collar that push fits over trap body of concrete floor drains to create a watertight seal.

Features

Floor Type - Concrete - Tile Floor Finish Waste Outlet - Single Collar Location - Central - Push Fit Stretch Collar Fit


Includes


Waterproof Membrane Gasket Waterproof Polycement Install Squeegee


<u>Size</u>	<u>Code</u>
Easy Fix Kit, FLEX < 1200mm	008 00276
Easy Fix Kit, FLEX < 2000mm	008 00277
Easy Fix Kit, MULTI <1200mm	008 00278
Easy Fix Kit, MULTI < 2000mm	008 00279


LINEAR FLOOR GULLYS


DRAWINGS






















18



WATERPROOFING

Membranes are critical waterproofing barriers used when building showers & like all defensive measures is most effective when in multiple layers.

: Always the first defensive layer, reduce available gaps • The Floor Finish for water to seep through by using large format tiles or

• Grout : Fill gaps with a higher quality grout to further reduce the

risk of leaks.

• Waterproof Membrane : Applied to the floor & walls, our dedicated membranes are superior, as boards add unnecessary thickness & are

often not waterproof.

Comprehensive testing confirms there are 2x solutions that meet our core values.

- : Easy to fit with tile adhesive, this professional membrane Sheet Membrane (AquaeGUARD)
 - creates a barrier to stop all water seepage.
- : A waterproof gel coating applied by brush or roller, this · 'Rubber" Paint

is the simplest solution to understand & use. (AquaeSEAL)

Quick & easy to apply, creating a waterproof barrier & stopping substrates from degrading, our membranes are flexible, cost effective & can be used on all substrates.

INDEX

P20 - AquaeSEAL™

P21 - AquaeGUARD™

P22 - EDGESeal™

P22 - HOW TO Waterproof

ALL FLOORS & WALLS

AquaeSEAL™ Kits

Project sized kits of waterproof gel coating and joint sealing tape packed together in convenient boxes

Kits are suitable for:

- Single standard size showers (UNO)
- Larger size showers (MEDIO)
- Additional components (see AquaeSEAL) can be added on demand

Features

- Floor Type Floor Finish
- Timber & Concrete - Below Tiles or Stone
- Roller or Brush Application

Includes

Waterproof Gel Coating Joint Sealing Tape Internal Corner Instructions

Size

UNO Waterproofing Kit 5m

Code 099 00074 099 00075 MEDIO Waterproofing Kit 10m



AquaeSEAL™ Kits



AquaeSEAL™

Premium quality range of individual components used to waterproof & seal walls & floors when building showers and

Gaps and cracks are 1st covered in Joint Sealing Tape & specially made collars. Waterproof gel coating is applied by roller or brush onto floors & walls.

Specially designed for tiles or stone, AquaeSEAL provides an ideal surface for adhesive to grab to.

Features

- All Floors Floor Type - All Walls Walls **Finish** - Tile & Stone Coverage - Min 5m² - Brush / Roller Application

Technical Data

Jointing Tape Width

- 100mm

- 5m, 10m, 25m & 50m Length - Small, Large Collars - Internal, External Corners

Membrane R.P Container

- 6 kg Tub - Gel Coating Membrane

Membrane - Dispersion

Type Style - Thixotropic - Approx. 3-5 hours **Drying Time**

<u>Code</u>

Waterproofing Tanking - R.P Waterproof Joint Seal Tape, 5m 004 00050 Waterproof Joint Seal Tape, 10m 003 00052 Waterproof Joint Seal Tape, 25m 003 00053 Waterproof Joint Seal Tape, 50m 003 00054 Waterproof INTERNAL corner 003 00055 Waterproof EXTERNAL corner Waterproof Joint Seal Tape, Wall 003 00059 Waterproof Joint Seal Tape, Floor 003 00060



WATERPROOFING SYSTEMS

ALL FLOORS & WALLS

AquaeGUARD™ Kits

Combining the key components & accessories from the AquaeGUARD range, these convenient project size kits will allow you to confidently waterproof regular (5m) or large (10m) shower structures. Choose additional components from the standard range as required.

Features

Floor Type Floor Finish

- Timber / Concrete - Tile

Application

- Use Tile Adhesive - 1m Wide Rolls

Size

<u>Includes</u>

Membrane -1 x 5m / 1 x 10m Joint Sealing Tape - 1 x 10m / 1x 15m Corner - 1x Internal

Instructions

Size Waterproofing Kit 5m Waterproofing Kit 10m <u>Code</u> 007 00513

007 00514



AquaeGUARD™

AquaeGUARD™

This German range of professional waterproofing membranes is designed especially for tiles, natural stone & mosaic. Ultra thin sheet membrane protects all floors & walls from damage by leaks. This excellent membrane stops penetration by water and steam, protecting the building from damage.

- AquaeGUARD™ Floor is a decoupling & sealing membrane for the floor only
- AquaeGUARD™ Universal is used on both floors and walls

Features

Floor Type Floor Finish Material

- Timber / Concrete

- Tile / Stone - Polyethylene / Polypropylene

Thickness Adhesive **Curing Time**

Size UNIV - 0.5mm - Cementious, powder Start tiling immediately

Application

AquaeGUARD™ - Floor Only

Floor AquaeGUARD™ Universal

- All Floors & Walls

<u>2</u>	<u>Code</u>
ERSAL, Membrane Roll 5m	007005
'ERSAL, Membrane Roll 10m	007005

00700503

00700504

00700508

00700509

00700510

00700506

00700507

00700505

UNIVERSAL, Membrane Roll 30m 00700502 FLOOR, Membrane Roll 5m FLOOR, Membrane Roll 30m Joint Sealing Tape, 10m Joint Sealing Tape, 15m Joint Sealing Tape, 50m **INTERNAL Corner EXTERNAL** Corner Gasket, Floor Collar **Bridging Collar, Pipe**

How to....WATERPROOF

1... Fit structural components

2-4... Apply joining tape accessories to cover all gaps & joists.

AquaeSEAL

5a... Mix & prepare waterproof gel

6a... Apply evenly across surface

7a... Apply 2nd coat at 90 degrees


AquaeGUARD

5b... Cut to size & fix membrane to floor **6b...** Fold membrane up walls & overlap membrane on wall

7b... Continue horizontal overlaps up walls

ALL

8... Tile & Grout





EDGESeal™

Flexible & stretchy membrane to stop leaks by permanently sealing baths & shower trays to walls behind tiles.

With a fleecy texture to grab to tile adhesive, this tape has a self adhesive strip along 1x side.

Technical Data

Lengths

- 120mm Wide - 2.0m (Showertray) - 2.85m (Showertray / Bath)


- 3.3m (Large Bath) - 20.0m (Trade Pack)

<u>Includes</u>

Tape roll with self adhesive edge

<u>Size</u>		Code
EDGESeal™, REGU	LAR 2.0m	007 0051
EDGESeal™, MEDIU	JM 2.85m	007 0051
EDGESeal™, LARGI	E 3.3m	007 0051
EDGESeal™, TRADI	E 20.0m	007 0052





Installation Systems - eForm 22 Formers

When fitting linear drains in a custom made shower, a common concern is the floor gradient, needed to direct water to the drain.

Comprehensive testing in Germany shows the fall for linear drains should be different to single point gullys.

The easiest method to correctly build the gradient is to use eForm™ 22 Gradient Boards (also known as floor formers.)

INDEX

P24 - Model A

P24 - Model V

P25 - Model B

P25 - Model C

P25 - Model D

P26 - HOW TO...Install a gradient with

eForm™ 22

GRADIENT FORMERS



TIMBER FLOORS

eForm™ 22 Model B

Trimable rectangular board to extend Model A & Model V by 500mm to a total of 1500mm along the finished floor level

Features

Floor Type Floor Finish Material

- Timber - Tile / Stone

- Hardcore™ - Mineral Polycement Waterproofing

Technical Data

Width Length Height


- 1000mm - 500mm - 22mm > 30mm

<u>Includes</u> **Gradient Board**

Instructions

<u>Size</u>

eForm™ 22, Model B HOW TO..., see page P.26 Tech Drawing, see page P.27 <u>Code</u> 005 00171





<u>eForm™ 22 Model C</u>

Trimable rectangular board to extend Model A & Model V by 350mm to one side.

Features

Floor Type Floor Finish Material Waterproofing - Timber - Tile / Stone - Hardcore™ - Mineral Polycement

Technical Data

Width Length Build-In Height

- 350mm - 1000mm - 22mm > 6mm

Includes

Gradient Board Instructions

<u>Size</u> eForm™ 22, Model C <u>Code</u> 005 00172

HOW TO..., see page P.26 Tech Drawing, see page P.27

eForm™ 22 Model D

Trimable rectangular 2x part board to extend Model A & Model V by 700mm to one side.

Features

Floor Type Floor Finish Material

- Timber - Tile / Stone

- Hardcore™ - Mineral Polycement Waterproofing

Technical Data

Width Length Build-In Height - 700mm - 1000mm

- 22mm - 6mm

Code

005 00173

Includes

Gradient Board Instructions


> Size eForm™ 22, Model D


HOW TO..., see page P.26 Tech Drawing, see page P.27

1000




INSTALL a GRADIENT using eForm™ 22

















































Bathroom Engineering is the partner of choice for all bathroom design & installation professionals. As a business to business specialist, we supply trade companies with not only the very best products, but also offer expert support for designers, contractors, architects, installers, & developers.

BROCHURES include....

- Bathroom Electrical
- Pre-Formed Shower Trays
- Structural Components



DEALER

Bathroom Engineering™
Priory Park
Chewton Mendip
Somerset
Bath
BA3 4NT

BA3 4NT

T +44(0)1761 241133 F +44(0)1761 241134

sales@bathroom-engineering.co.uk www.bathroom-engineering.co.uk



